


## Sluoksniuotai klijuota mediena

### Matmenys

- ✓ Standartiniai skerspjūviai
- Specialūs užsakymai

Aukštis (mm) → Plotis (mm) ↓	120	140	160	180	200	220	240	260	280	320	360	400	440	ir t. t. pride- dant +40mm
60	✓	●	✓	●	✓	●	✓	●	✓	✓				
80	✓	●	✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
100	✓	●	✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
120	✓	●	✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
140		●	✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
160			✓	●	✓	●	✓	●	✓	✓	✓	✓	✓	
180				●	✓	●	✓	●	✓	✓	✓	✓	✓	
200					✓	●	✓	●	✓	✓	✓	✓	✓	
220						●	✓	●	✓	✓	✓	✓	✓	
240							✓	●	✓	✓	✓	✓	✓	



Ilgis: iki 36 m  
Didžiausias aukštis: 2,3 m

### Homogeninės sluoksniuotai klijuotos medienos stiprumo klasės, norminio stiprio, standumo ir tankio rodikliai EVS-EN 14080:2013

Stiprumo klasė		GL24h	GL28h	GL32h
Stiprumo savybės, N/mm <sup>2</sup>				
Lenkimo stipris	fm,g,k	24	28	32
Tempimo stipris	ft,0,g,k	19.2	22.3	25.6
	ft,90,g,k	0.5	0.5	0.5
Stipris gniuždant	fc,0,g,k	24	28	32
	fc,90,g,k	2.5	2.5	2.5
Šlyties (kirpimo) stipris	ft,0,g,k	3.5	3.5	3.5
Standumo savybės, N/mm <sup>2</sup>				
Elastingumo modulis	E0,g,mean	11500	12600	14200
	E0,g,05	9600	10500	11800
	E90,g,mean	300	300	300
Šlyties modulis	Gg,mean	650	650	650
Tankis, kg/m <sup>3</sup>	rg,k	420	460	490